

## WHAT IS CLAIMED IS:

1. A strap buckle apparatus fastened to a lock hole of a notebook computer, said strap buckle apparatus linking to said notebook computer and a  
5 strap, said strap buckle apparatus comprising:

a rotation hub;

a base, connected to said strap, said base having an opening; and

a rotation plug, one end of said rotation plug inserted into said lock hole  
to lock or unlock said strap buckle apparatus, the other end of said rotation plug  
10 fixed to said rotation hub via said opening, wherein said rotation hub controls  
said rotation plug for locking or unlocking said lock hole.

2. The strap buckle apparatus of claim 1 further comprises a protection  
pad placed between said base and said rotation plug, said protection pad  
15 prevents from scratching the surface of said notebook computer.

3. The strap buckle apparatus of claim 2, wherein said protection pad is  
made of rubber.

20 4. The strap buckle apparatus of claim 1, wherein said rotation hub  
further comprises a clamp, to fasten said rotation plug to said rotation hub.

5. The strap buckle apparatus of claim 1, wherein said rotation hub  
further comprises a position pin, facing toward said base.

25

6. The strap buckle apparatus of claim 5, wherein said base further comprises a position groove to guide said position pin, and two ends of said position groove are carved deeper.

5           7. The strap buckle apparatus of claim 1, wherein said base further comprises a strap holder to connect to said strap.

8. A strap buckle apparatus fastened to a lock hole of a notebook computer, said strap buckle apparatus linking to said notebook computer and a  
10 strap, said strap buckle apparatus comprising:

          a clamp;

          a rotation hub;

          a base, connected to said strap, said base having a first opening;

          a protection pad, having a second opening; and

15           a rotation plug, one end of said rotation plug inserted into said lock hole to lock or unlock said strap buckle apparatus, the other end of said rotation plug fixed to said rotation hub via said first and second openings, wherein said rotation hub controls said rotation plug for locking or unlocking said lock hole.

20           9. The strap buckle apparatus of claim 8, wherein said rotation hub further comprises a position pin, facing toward said base.

10. The strap buckle apparatus of claim 9, wherein said base further comprises a position groove to guide said position pin, and two ends of said  
25 position groove are carved deeper.

11. The strap buckle apparatus of claim 8, wherein said base further comprises a strap holder connecting to said strap.

5 12. The strap buckle apparatus of claim 8, wherein said protection pad is made of rubber.